

RFID settings

RFID can be set up to work with Soutron providing your hardware is SIP-2 compatible. Soutron LMS has been certified by [Bibliotheca](#) to work with their Lib er8 RFID software. It also works with products from [PSP Asset Protection](#) and [D-tech](#).

If you are interested in using RFID, please contact the [helpdesk](#) who will discuss your requirements and assist you with the setup process.

Caution! Making changes to the settings will break the connection with the terminal

Server Side Configuration

The configuration process requires some configuration at the server level, which is done by Soutron.

Application Configuration

To access **System Configuration Maintenance**, select **System Management > System Configuration Maintenance**.

Click on the RFID tab to display the page as follows:

System Configuration Maintenance Powered By Soutron

Actions: Save, Save and close, Cancel

Navigation: Auto Cat & Images, Review & Rating, API, YouTube Integration, External Mapping, My Account, ART Format, Acquisitions, PayPal, RFID

Fields: Login, Password, Host, Port (0)

The table below explains the function of each setting - Soutron will provide all the values for the settings:

Setting	Function	Default Value
Login	Login that the 3rd party RFID software will use to connect to Soutron	N/A
Password	Password that the 3rd party RFID software will use to connect to Soutron	N/A
Host	Host that the 3rd party RFID software will use to connect to Soutron. If you are self-hosting Soutron, the host field should be set as an IP address, which is not bound to any other website.	N/A
Port	Port that the 3rd party RFID software will use to connect to Soutron	0